


Ausführung C



Gummi-Metall-Puffer
mit beidseitigem
Innengewinde
Naturkautschuk
45°, 55°, 65°, 70° Shore



Artikel-Nr.	Ø d	h	Gewinde
C- 01010	10	10	M 4
C- 01015	10	15	M 4
C- 01020	10	20	M 4
C- 01515	15	15	M 4
C- 01520	15	20	M 4
C- 01530	15	30	M 6
C- 02020	20	20	M 6
C- 02025	20	25	M 6
C- 02030	20	30	M 6
C- 02520	25	20	M 6
C- 02525	25	25	M 6
C- 02530	25	30	M 6
C- 03020	30	20	M 8
C- 03025	30	25	M 8
C- 03030	30	30	M 8
C- 03040	30	40	M 8
C- 04025	40	25	M 8
C- 04030	40	30	M 8
C- 04040	40	40	M 8
C- 04025	40	25	M 10
C- 04030	40	30	M 10
C- 04040	40	40	M 10
C- 05025	50	25	M 10
C- 05030	50	30	M 10
C- 05040	50	40	M 10
C- 05045	50	45	M 10
C- 05050	50	50	M 10
C- 05080	50	80	M 10
C- 06030	60	30	M 10/12
C- 06040	60	40	M 10/12
C- 06050	60	50	M 10/12
C- 06060	60	60	M 10/12
C- 07045	70	45	M 10
C- 07055	70	55	M 10
C- 07045	70	45	M 12
C- 07525	75	25	M 12
C- 07530	75	30	M 12
C- 07540	75	40	M 12
C- 07545	75	45	M 12
C- 07550	75	50	M 12

Artikel-Nr.	Ø d	h	Gewinde
C- 07555	75	55	M 12
C- 07570	75	70	M 12
C- 10040	100	40	M 16
C- 10050	100	50	M 16
C- 10055	100	55	M 16
C- 10060	100	60	M 16
C- 10075	100	75	M 16
C- 100100	100	100	M 16
C- 12070	120	70	M 16
C- 12550	125	50	M 16
C- 12555	125	55	M 16
C- 15050	150	50	M 16
C- 15055	150	55	M 16
C- 15075	150	75	M 16
C- 16075	160	75	M 16
C- 200100	200	100	M 20